Lime Stuff Limited
tel: 01794 884294
email: info@limestuff.co.uk
web: www.limestuff.co.uk

PRODUCT DATA SHEET

Coarse Stuff

Description	A hot lime mixed mortar/plaster made with quicklime, water and a blend of aggregates.
1. Colour code	BL40 Chalk white
Aggregate blend	2 parts Wareham washed sharp sand, 1 part Newbury Grit sand,
2. Colour code	LS2 Oatmeal
Aggregate blend	1 part Frith End Blend, 1 part Wareham washed sharp sand, 1 part Newbury Grit sand.
Aggregate size	**<**4mm
Mix ratio	1:3 lime/sand
Uses	As an internal or external base coat.
Approximate Coverage	1m^2/25kg at 10mm thickness onto wooden lath. 1.2m^2/25kg at 10mm thickness onto solid substrate.
Shelf Life	Avoid exposure to excess heat or cold. Lime plaster matures and improves with age when kept sealed.
Units	25kg plastic bag.
Health and Safety	Contains Calcuim Hydroxide CA(OH)^2. **GHS07** Harmful/Irritant/Skin Sensitizer **H315** Causes skin irritation **GHS05** Corrosive **H318** Causes serious eye damage **Precautionary Statements** **P102** Keep out of reach of children **P262** Do not get in eyes, on skin, or on clothing **P280** Wear protective gloves/protective clothing/eye protection/face protection **P305+P310+P351** If in eyes rinse continuously with water for several minutes and immediately seek medical assistance **P302+P352** If on skin wash with plenty of soap and water
Observations	Recommended to be used by professional tradesmen experienced in the application of lime plasters. Use at temperatures above 5 degrees and below 25 degrees.
Technical Advice	Call 01794 884294 or email info@limestuff.co.uk